

Desmol

Release powder

Waxes, micronized pigments and additives.



Product

- For immediate desmolding
- Does not stick to the mould
- For ageing the pavement
- Excellent yield

Characteristics

- Release agent for printed concrete and mortars.
- Prevents the mortar from sticking to the mold.
- Used for aging the floor or wall.

Performances

- Water solubility: insoluble
- Separating temperature: 400°C
- PH: 8-9 (50 g/L water)
- No toxic

Usage way

Sprinkle on concrete or mortar in a plastic state.

Apply a layer covering the entire surface.

Avoid application when the concrete has excess surface water, and white areas would be formed very difficult to control.

Do not apply with strong wind.

Associated products

*Impreso

*Release agent-l2



Packaging

10 liter drum
675 l pallet (27 drums)

Color

10 standard colors



Consumption

0,15 – 0,2 l/m²

** This consumption may oscillate according to the application.*

Preservation

In the closed original container and sheltered from outdoor and humidity.

! IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.