

Pavi-traffic

Painting for horizontal signalling

Quick drying painting and great resistance to abrasion.



Product

- Very resistant to abrasion.
- Easy application.
- Quick drying.
- Admits the silica arid aggregate.

Usage

- Horizontal signalling for roads, parkings, warehouses, etc...
- Admits the little pearls sprinkling, in a proportion between 0.4 and 0.5 kg. per 1 kg. painting **Pavi-traffic**.

Enforcement

- Application temperatures: 10-30°C
- With spray devices used for signalling.
- Do not apply with rain risk or frost possibility.

Performances

- Binder: Plastified Chloro-rubber .
- Pigment: Pigments coverings and extending.
- Brightness: Silky.
- Specific weight: From 1,55 to 1,75.
- Viscosity Stomer at 25°C: 80 – 90 units Krebs.
- Dry for traffic at 25°C: 30 minutes.
- Disolution: Diluting epoxy.

**All the information described has been obtained in standard essays and it can oscillate depending on the workplace conditions.*



Packaging

5 and 30kg packages

Color

White and yellow.
Others on demand.

Consumption

6-8 m²/kg approximately
(1 coat and depending on the support)

Preservation

In original closed container, protected from weather and humidity:
1 year. weather and humidity: 1 year

⚠ IMPORTANT

The observations and prescriptions of this data sheet, although corresponding to our best experience, should be considered, in any case, purely indicative, and should be tested by exhaustive practical applications; therefore, before using the product, the user must establish whether or not it is suitable for the intended use, and assumes all liability that may arise from its use. Once the product has been handled or applied, the manufacturer shall not assume any claim whatsoever, nor any liability as to the manner, mode and conditions of application.