

Pintura Acrilica

Smooth acrylic coating for interiors and exteriors

Acrylic paint for decoration and protection of facades and single-layer mortars, both indoors and outdoors.



Characteristics

- Appearance: silky matte.
- Relative humidity: <80%.
- Density: 1,52 +/- 0,050 kg/l.
- Diluent: water
- Drying: ≥1 hour.
- Recoating: 3-4 hours.
- Application: by roller, brush, airless...
- Flash point: Not applicable

**These results are standard test results and may vary depending on site conditions.*

Supports

- **Revislant, Revistamp-sec**, concrete, conventional mortar, wood and plaster.
- On already painted substrates or old coatings, in restoration in good condition and perfectly adhered to the substrate.

Support preparation

- The substrates should be solid, dry (set if newly constructed), with good flatness, absorbent, not contaminated with oils, detergents, powders or other substances.
- Evaluate the most suitable type of mechanical preparation (abrasion or shot blasting machine).
- Eventual cavities and slight anomalies can be repaired with **Pavigrout** or putty.
- On weak or dusty mortars, it is advisable to pressure wash and apply **silicate hardener** until the desired hardness is achieved.

Enforcement

- On properly prepared, clean and dry surface.
- On a very absorbent substrate, apply 1-2 coats of **F-300** fast primer.
- Before use, stir well the content of the container.
- Apply in 2 coats:
 - 1st pass, dilute with ±20% water.
 - 2nd pass, dilute with ±10% water.

Observations

- DO NOT APPLY:
 - A temperaturas inferiores a 7°C.
 - Con posibilidad de lluvia, hielo, deshielo.
 - Con humedad relativa ≥80%.
 - Sobre superficies frágiles o inestables y sin garantías.

⚠ IMPORTANT

The observations and prescriptions of this data sheet, although corresponding to our best experience, should be considered, in any case, purely indicative, and should be tested by exhaustive practical applications; therefore, before using the product, the user must establish whether or not it is suitable for the intended use, and assumes all liability that may arise from its use. Once the product has been handled or applied, the manufacturer shall not assume any claim whatsoever, nor any liability as to the manner, mode and conditions of application.



Packing

6 and 22 kg packages

Colors

White (others on request)
(can be colored with Universal Dye)

Consumption

22 kg = 60-90 m² (2 passes and according to absorption)

Preservation

In unopened original container (5-35°C), protected from weather and humidity: 2 years

Associated products

- Silicato
- Pavigrout
- F-300
- Masilla