

Mortecril fund®

Background regulator for acrylic mortar

Binders, mineral pigments and organic and inorganic additives.



Product

- To regulate the color and absorption.
- Ready to use.
- Easy application.
- Excellent adherence.
- Color chart.

Observations

- To avoid transparencies in the final finish.
- Do not add any additive to the product.
- Consumption per m² can considerably oscillate depending on the support absorption.
- Fit to be recovered.

Performances

- Capillary water absorption: 0.04 kg (m² · min 0.5)
- Adhesion: > 1.0 N/mm
- Application temperatures: 5 - 30 °C
- Material: Acrylic polymer
- Diluting: water

**These results can oscillate depending on the workplace conditions.*

Enforcements

- Color primer for regularization and fund absorption before the acrylic coating application associated with the external thermal isolation for outdoors **Pavitherm (SATE + ETICS)**.

Supports

- **Pavitherm System (SATE) (ETICS), Revislant, Revistamp-Sec**, concrete, conventional mortar, wood and plaster...
- Over already painted support or old coatings, in good condition restoration and perfectly adhered to the support.

Execution conditions

- The supports must be flat, stable, resistant and clean.
- Application over absorbent support.
- To avoid transparency and changes in tone, always use the Mortecril background with the same color or similar to the final coating.
- Depending on the chosen color and support absorption, it could be necessary to apply 2 layers.
- The regularization layer with **Mortecril fund** must be completely dry before the application of **Mortecril**.

Mortecril fund®

Background regulator for acrylic mortar

Usage way

Remove the content until obtaining a perfect homogenize.

Once the container has been opened, before use, stir the entire contents with a whisk until a homogeneous mass is obtained.

Apply with roller, brush...

It can be diluted with water.

Drying time: 1 – 3 hours

Cleaning tools: water

Associated products

*Mortecril micro

*Mortecril line

*Mortecril rustic

*Revislant (Pavitherm SATE + ETICS)

*Revistamp sec



Packaging

25 kg plastic drum
600 kg pallet (24 drums)

Colors

Color chart **Mortecril**

Consumption

0,2 - 0,3 kg/m² (depending on the support absorption)

Preservation

In original container closed and sheltered from
outdoor and humidity: 1 year

⚠ IMPORTANT

The observations and prescriptions of this data sheet, although corresponding to our best experience, should be considered, in any case, purely indicative, and should be tested by exhaustive practical applications; therefore, before using the product, the user must establish whether or not it is suitable for the intended use, and assumes all liability that may arise from its use. Once the product has been handled or applied, the manufacturer shall not assume any claim whatsoever, nor any liability as to the manner, mode and conditions of application.