

Mortecril Rustic®

Acrylic mortar, rustic and striped finish

Silicates, acrylic resins, loads, mineral pigments and organic and inorganic additives.



Product

- Rustic finishes.
- Excellent adherence.
- Anti-mold – anti-moss.
- Ageing resistant.
- Cleanable.
- Colors chart.

Observations

- Do not apply over horizontal surfaces or less than 45° inclined surfaces.
- Protect the coating superior edges from rainwater penetration.
- Do not add any additive to the mortar.
- Consumption per m2, can considerably oscillate depending on the support planimetry.

Characteristics

- Application thicknesses from 2 - 4 mm.
- Troweled time: 10-20 minutes.
- Dry touch: 3-6 hours.
- Total hardening time: 12- 24 hours.

** These results are contemplated with 20°C and they can oscillate depending on the ambient temperature.*

Performances

- Paste density: 1905 kg/m3
- Drying shrinkage: 4.50 mm/m
- Flexural elasticity module: ≥ 27 MPa
- Dynamic elasticity module: ≥ 200 MPa
- Flexural strength: ≥ 1.5 N/mm2
- Compressive strength: ≥ 18 N/mm2
- Capillary absorption of the mortar support: 12g (m2xs0,5)
- Adhesion on mortar: ≥ 2 N/mm2
- Water permeability (48h): 0.04 ml/cm2
- Fire behavior: non-combustible

***These results can oscillate depending on the workplace conditions.*

Enforcements

- High performances acrylic coating with thick layer for decoration, waterproofing and protection from all kind of facades, outdoors and indoors.
- New construction and rehabilitation.
- Water and dirtiness repellent.
- Anti-mold- anti-moss.
- In walls and ceilings.
- Suitable with the majority of supports.

Supports

- **Revistamp-Sec**, concrete, conventional mortar, wood and plaster.
- For finishes associated with the isolation systems for outdoors **Pavi-Therm**, apply over **Revislant**.
- Over already painted support or old coatings, in good condition restoration and perfectly adhered to the support.

Recommendations

- Application temperatures from 5 to 30°C.
- Do not apply with direct insolation, strong wind or rain or frost possibility.
- Protect the zones where product splashes can take place, like windows, floors ...
- Clean the utensils with water.

Execution conditions

- The supports have to be flat, stable, resistant and clean.
- Application over excellent planimetry supports.
- Over very absorbent or easily disaggregating supports, apply previously a primer layer **F-300** diluted with water (1 part **F-300**, 3 water parts).
- Always apply a primer coat **Mortecril** background so that there are no possible transparencies, 24 hours after **Mortecril rustic** can be applied.
- Use adhesive tape to delimit the work joints or decorative quartering.
- In case of applying in great extensions, prevent additional manpower to avoid the joints appearance inside the same surface.
- Do not interrupt application once started, unless performing a work or decorative joint.

Mortecril Rustic®

Acrylic mortar, rustic and striped finish

Usage way



Mortar is provided ready to use.

Once the package is opened and before using, remove all the content with a whisk until obtaining a homogeneous mass.



Apply **Mortecril rustic** with stainless steel trowel or with projecting pistol with a 2-3mm thickness in all its points.

Projected in a drop way and finish pressed

Use adhesive tape to perform the work joints or any imitation brick, stone ...



Associated products

*Mortecril fund

*Mortecril micro

*Mortecril line

*Revislant (pavitherm)

*Revistamp sec M-120



Packaging

25 kg drum
600 kg pallet (24 drums)

Colors

28 colors chart

Consumption

2-4 kg/m², applied with trowel.
2-3 kg/m², applied with projecting pistol.

Preservation

24 months (20°C) from the fabrication date, in the closed original package and sheltered from outdoor and humidity.

! IMPORTANT

The observations and prescriptions of this data sheet, although corresponding to our best experience, should be considered, in any case, purely indicative, and should be tested by exhaustive practical applications; therefore, before using the product, the user must establish whether or not it is suitable for the intended use, and assumes all liability that may arise from its use. Once the product has been handled or applied, the manufacturer shall not assume any claim whatsoever, nor any liability as to the manner, mode and conditions of application.