

# Paviseal 505

Relief enhancer for surfaces.

Consolidant in aqueous dispersion with special additives, free of plasticizers.



## Product

- For consolidating old mortars or those with low cement content.
- Waterproofs and rejuvenates aged concrete.
- Compatible with new mortars.
- Good penetration on porous surfaces.

## Enforcements

- Silicate- and acrylic polymer-based coating for hardening surfaces when concrete or mortar is degraded.
- The mineralization process develops progressively over several weeks.
- High penetration capacity.

## Supports

- Any cementitious surface in a state of degradation.
- Old concrete / exposed aggregate / brushed finish.
- Curbs.
- Cladding / paving blocks..

## Recommendations

- The surface must be clean, free of dust, and free from loose or powdery parts.
- Avoid application under direct sunlight, wind, risk of rain, or frost.
- Protect all areas where product splashes may occur, such as windows and floors..

## Usage way - dosage

- Shake the product well before application and dilute with 3 to 5 parts of clean water, depending on the substrate to be enhanced or the desired finish.
- In windy or very hot weather, dampen the surface before applying the product.
- Do not apply if there is a risk of rain, frost, or thawing.
- Allow the product to cure for 1-2 hours before applying the final coating.
- \*\* These times may vary significantly depending on ambient temperature.

## Observations

- Application temperature: 10°C - 30°C

## ⚠ IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether or not it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.



## Packaging

1kg – 5kg

## Consumption

±0.200 kg/m<sup>2</sup> per coat, depending on porosity.

## Color

Milky white

## Preservation

In the closed original container and sheltered from outdoors and humidity: 1 year