

Silica sand

Washed silica sand

Silica sand, with clean compensated grain size and dry on the oven



Product

- Controlled grain size
- Suitable for industrial use
- Suitable for mortar and painting reinforcement
- Suitable for self leveling floors and epoxy

Enforcements

- For high abrasion resistance floor elaboration.
- To perform anti-slip surfaces and increase the adherence in posterior layers.
- As filling to elaborate the epoxy self leveling mortars.
- Ideal to clean metallic surfaces before applying a covering.
- To elaborate and reinforce high quality repair mortars.
- As covering over bituminous for pedestrian traffic protection.

Performances

- Specific gravity: 2.65 g/cm³
- Humidity content: $\pm 0,1$ %
- Bulk density: 0,93-1.1 g/cm³
- Compact density: 1,4-1,55 g/cm³
- Paste life: 30 minutes
- Burnt point: 32,5
- pH: 8.4
- Behavior against fire: A1 euroclass

**Performances are contemplated depending on the lots.*

Associated products

- Epoxy resins



Packing

25 kg sack

Consumption

Depending on the use.

Color

Standard: brown.
Others: on demand.

Preservation

Does not expire; keep it in closed original container, sheltered from outdoors and humidity

⚠ IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.