

Release Agent-L2

Liquid separating agent

Liquid release agent ready to use in an organic medium and fat materials.



Product

- For immediate separation
- Prevents the efflorescence appearance
- Colorless and breathable
- Prevents the mold from sticking with the fresh mortar.
- For pavements and facades

Characteristics

- Liquid release agent for the superficial textured and stamping treatment.
- On fresh concrete and mortar, stamped concrete, thematic rock, single-layer mortars...

Usage way

- Application temperatures: 5- 35°C.
- Spray in a homogeneous way over the mold to be used.
- Print or texture with the selected mold.
- The in exceeding application could cause tone changes.
- With dark tones (façades), it is necessary to apply a water-repellent **Dye** coat to homogenize the finish tonality.
- Protect all the surfaces that are not going to be water-repellent with the product and/or supports that are not concretely cementitious.

**These results can considerably oscillate depending on the workplace conditions.*

Performances

- Density, 25°C 0.85 g/cm3

Associated products

*Concrete and mortar



Packaging

20 kg drum
480 kg pallet (24 drums)

0,1 - 0,2 kg/m2

Color

Yellowish

Preservation

In the closed original container and sheltered from outdoor and humidity: 1 year

⚠ IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.