

Paviseal-700

Water-repellent oleofugant

Compound by Fluorinated Silane-Siloxane in water solution for the construction material treatment giving a finish repellent to water and oils.



Product

- Repellent to water and oils effect.
- Does not modify the existing color.
- Avoid efflorescences
- Breathable.
- Mortars, marble, stone, clinker brick.

Enforcements

- Excellent penetration.
- Avoid the stains appearance.
- To be used for the water-repellent and oleofugant of materials **Stone feel**
- – **Stylfloor – Pavistamp floor**, Pavicem, marble, natural stone, granite, mortars, brick...
- Permeability to water steam.

Usage way

***Always perform tests before using the product**

***Dilute with water;**

1 part of **Paviseal-700** / 7-14 water parts.

- In recently worked surfaces, wait at least 30 days, before proceeding to the treatment.

- Apply 1-2 pass with mop, airless, conventional spray..., after 8 hours (minimum), proceed with the brightening machine ultra quick until obtaining the more uniform to the support finish

- Generally, an only pass is enough, over porous surfaces, if it was necessary, a second pass can be applied when the brightness effect of the first one disappears.

- Avoid direct insolation.

**All the information described has been obtained with standard essays and can oscillate depending on the workplace conditions and the absorption of each product to be treated.*

Observations

- The support must be dry, healthy, clean and without dust.
- Avoid splashes in the eyes, mucous and skin contact
- Use protection glasses and gloves.
- Protect all the surfaces that are not going to be waterproofed and/or supports that are not concretely cementitious.

Performances

- Active material: 45%
- Flashpoint: > 100°C
- Viscosity (to 25°C): < 50 mPas (cP)
- Density (a 25°C): approx. 1.1 g/cm
- Diluting: water

! IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.



Packaging

5 kg drum
360 kg pallet (72 drums)

Colors

Milky white

Consumption

(once diluted)

1kg: between 5-25 m2 / 1 pass and depending on support

Preservation

(5- 25°C)

In the closed original container and sheltered from outdoors and humidity: 6 months

Associated products

Stone feel - Stylfloor - Terrazo
Pavistamp floor - Micro cement