

Paviseal Ready 250

Conventional acrylic emulsion

Emulsion in aqueous dispersion for the protection of concrete and mortar pavements.



Product

- For sealing concrete pavements and protecting facades.
- Good abrasion resistance.
- For maintenance and conservation.
- Water based.
- Indoors and outdoors.

Characteristics

- Water-based acrylic emulsion for curing, protecting floors and mortars.
- Transparent, waterproof and breathable.
- Enhances the color.
- Glossy finish.

Recommendations

- Application temperatures between 10 and 30°C (measured on the pavement).
- It can be applied on wet floors (free of puddles of water).
- Roller or airless.
- Application in 2-3 passes is recommended.
- It can be used over time for the conservation and maintenance of any concrete floor, whether smooth, decorated or stamped.
- Avoid application when there is a risk of rain or very humidity, where there is a risk of frost or direct sunlight.

Usage way

- The area to be treated must be completely clean, free of dust, grease...
- Application without overloads in 2-3 passes.

**Consumption is from standard tests and may vary considerably depending on the absorption of the concrete or mortar and the conditions of installation.*

Performances

- Density: 1.5 g. /cm³
- P.H.: 7.0 – 9.0 UNE – EN 1262
- Color: Milky White
- Touch dry: >2 hours
- Pedestrian traffic: > 24 hours
- Road traffic: >7 days

** These times are contemplated at 20°C and may vary depending on the ambient temperature.*

⚠ IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.



Packaging

20 liter drum
480 liter pallet (24 drums)
1000 liter drum

Color

White (once dry, transparent)

Consumption

(as sealing resin)

0,2-0,3 l/m² (1 pass)

Preservation

In closed original container (without added water)
protected from the elements and humidity: 6 months

Associated products

Concrete and mortar