

# Protec facades S

## Water-repellent

Water repellent ready to use, with silicone base.



### Product

- Ready to use.
- Pearl effect.
- Rain water penetration repellent.
- Only on vertical supports.

### Enforcements

- Excellent penetration.
- Specially formulated to obtain a quick dry in all the neutral and alkaline surfaces appearing the Pearl effect in the hours following to its application.
- Breathable.

### Usage way

- Application temperature: 5-30 °C.
- Product ready to use.
- The support must be dry, healthy, clean and free of dust.
- On mortar, concrete, completely dry and set >28 days.
- Apply by brush, roller, spray or gun.
- In general, a single pass is sufficient, in the case of very porous surfaces, the application of a second pass is necessary, as soon as the shiny effect of the first one disappears.
- After rain, wait at least 24 hours before applying the product.

### Observations

- Do not apply with wind or rain risk.
- Avoid splashes in the eyes, mucous and skin contact.
- Use protection glasses and gloves.
- Protect all surfaces that are not going to be treated with the product and / or supports that are not specifically cementitious.
- It contains solvents.

### Performances

- Active material: aprox. 6%
- Density 25°C: 0.85 g/cm<sup>3</sup>

*\*All the information described has been obtained with standard essays and it can oscillate depending on the workplace conditions.*



### Packaging

20 liters drum  
480 liters pallets (24 drums)

### Consumption

Advisable: 1 liter = ±3 m<sup>2</sup> (1 layer)

### Colors

Yellowish

### Preservation (20-25 °C)

In the closed original container and sheltered from outdoors and humidity: 1 year

## ⚠ IMPORTANT

The observations and prescriptions of this technical sheet, even corresponding to our best experience, should be considered, in any case, purely indicative, and must be tested by exhaustive practical applications; Therefore, before using the product, whoever is going to do it must establish whether it is suitable for the intended use, and assumes any responsibility that may arise from its use. Once the product is handled or applied, the manufacturer will not assume any claim, nor will it be responsible for the form, mode and conditions of application.